


B800008



► 主要技术特性 (Main Specifications)

- 适用导线规格 (Applicable wire) : AWG22#~18#
- 适用基板厚度 (Applicable PC board thickness) : 1.6mm
- 温度范围 (Temperature range) : -25°C~+85°C
- 额定电压 (Voltage rating) : 250V AC, DC
- 额定电流 (Current rating) : 3A AC, DC
- 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstanding voltage) : 1500V AC/minute

材料及电镀规格 Material and Finish


| 型号 Type | 材料 Material | 材料厚度 Material Thickness | 电镀规格 Finish |
|-------------|---------------------|-------------------------|---------------|
| 插座 WAFER | 塑胶 HOUSING | PA66 UL94V-0 | N/A |
| | 针 PIN | 黄铜 Barss | 镀锡 Tin-plated |
| 孔座 HOUSING | PA66 UL94V-0 | — | N/A |
| 端子 TERMINAL | 锡青铜 Phosphor bronze | 0.3mm | 镀锡 Tin-plated |

产品尺寸图 Product size chart

 单位: mm 一般公差: ± 0.20

TERMINAL

B800008-4 172093-M2



WAFER

B800008-1-02

B800008-2-02 N2420-4202

