


B620001

L6.2



- ▶ 主要技术特性 (Main Specifications)
- ▶ 适用导线规格 (Applicable wire) : AWG20#~12#
- ▶ 适用基板厚度 (Applicable PC board thickness) : —
- ▶ 温度范围 (Temperature range) : -25°C~+85°C
- ▶ 额定电压 (Voltage rating) : 300V AC, DC
- ▶ 额定电流 (Current rating) : 20A AC, DC
- ▶ 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- ▶ 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- ▶ 耐压 (Withstanding voltage) : 2000V AC/minute



材料及电镀规格 Material and Finish

型号 Type	材料 Material	材料厚度 Material Thickness	电镀规格 Finish
孔座 HOUSING	PA66 UL94V-0	—	N/A
端子 TERMINAL	锡青铜 Phosphor bronze	0.25mm	镀锡 Tin-plated

产品尺寸图 Product size chart

 单位: mm 一般公差: ± 0.20

TERMINAL

B620001-3
L6. 2-A

B620001-4
L6. 2-Y


HOUSING

极数 Circuits	公端胶座 Male Housing (for pin contact)	母端胶座 Female Housing (for socket contact)	母端胶座 Female Housing (for socket contact)
1	B620001-1-01F L6. 2R-01VF 	B620001-2-01 L6. 2P-01V 	—
2	B620001-1-02F L6. 2R-02VF 	B620001-2-02 L6. 2P-02V 	—
	B620001-1-02 L6. 2R-02V 		—

B620001

L6.2

HOUSING

极数 Circuits	公端胶座 Male Housing (for pin contact)	母端胶座 Female Housing (for socket contact)	母端胶座 Female Housing (for socket contact)
3	B620001-1-03 L6.2R-03V 	B620001-2-03 L6.2P-03V 	
6	B620001-1-06 L6.2R-06V 	B620001-2-06 L6.2P-06V 	B620001-2-06 L6.2P-06V