

B620002

VL



▶ 主要技术特性 (Main Specifications)

- ▶ 适用导线规格 (Applicable wire) : AWG20#~14#
- ▶ 适用基板厚度 (Applicable PC board thickness) : —
- ▶ 温度范围 (Temperature range) : -25°C~+85°C
- ▶ 额定电压 (Voltage rating) : 300V AC, DC
- ▶ 额定电流 (Current rating) : 20A AC, DC
- ▶ 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- ▶ 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- ▶ 耐压 (Withstanding voltage) : 2000V AC/minute



材料及电镀规格 Material and Finish

型号 Type	材料 Material	材料厚度 Material Thickness	电镀规格 Finish
孔座 HOUSING	PA66 UL94V-0	—	N/A
端子 TERMINAL	磷青铜 Phosphor bronze	0.25mm	镀锡 Tin-plated

产品尺寸图 Product size chart

 单位: mm 一般公差: ± 0.20

TERMINAL

B620002-3
VL-A

B620002-4
VL-Y












HOUSING

极数 Circuits	公端胶座 Male Housing (for pin contact)	母端胶座 Female Housing (for socket contact)	锁扣 Actuator
1	B620002-1-01F VLR-01VF 	B620002-2-01 VLP-01V 	B620002-5-01 VLS-01V
2	B620002-1-02 VLR-02V 	B620002-2-02 VLP-02V B620002-2-02A VLP-02VA 	B620002-5-02 VLS-02V

B620002

VL










HOUSING

极数 Circuits	公端胶座 Male Housing (for pin contact)	母端胶座 Female Housing (for socket contact)	锁扣 Actuator
3	<p>B620002-1-03 VLR-03V</p> 	<p>B620002-2-03 VLP-03V</p>  <p>B620002-2A-03 VLP-03V/A</p> 	<p>B620002-5-03 VLS-03V</p> 
	4	<p>B620002-1-04 VLR-04V</p> 	<p>B620002-2A-04 VLP-04V</p>  <p>B620002-2-04A VLP-04VA</p> 
<p>B620002-1-04N VLR-04VN</p> 		<p>B620002-2-04NA VLP-04VNA</p> 	<p>B620002-5-04 VLS-04V</p> 

B620002

VL



HOUSING

极数 Circuits	公端胶座 Male Housing (for pin contact)	母端胶座 Female Housing (for socket contact)	锁扣 Actuator
6	B620002-1-06 VLR-06V 	B620002-2-06 VLP-06V 	B620002-5-03 VLS-03V 
8	B620002-1-08 VLR-08V 	B620002-2-08 VLP-08V 	B620002-5-04 VLS-04V 
12	B620002-1-12 VLR-12V 	B620002-2-12 VLP-12V 	B620002-5-06 VLS-06V 

B620002

VL

TERMINAL

B620002-3A VL-A-B

B620002-4A VL-Y-B


HOUSING

极数 Circuits	公端胶座 Male Housing (for pin contact)	母端胶座 Female Housing (for socket contact)	锁扣 Actuator
2	B620002-1-02K VLR-02VK MG620874 	B620002-2-02K VLP-02VK MG610873 	B620002-5-02 VLS-02V
3	B620002-1-03K VLR-03VK MG620877 	B620002-2-03K VLP-03VK MG610876 	B620002-5-03 VLS-03V